



PIN	FUNCT	PIN	FUNCT	PIN	FUNCT	PIN	FUNCT
1	BP	70	BP	19	3E	52	3G
2	6E	69	6G	20	3D	51	3F
3	6D	68	6F	21	---	50	3A
4	6C	67	6A	22	---	49	---
5	DP5	66	6B	23	---	48	---
6	5E	65	5G	24	3C	47	---
7	5D	64	5F	25	---	46	3B
8	5C	63	5A	26	DP2	45	---
9	DP4	62	5B	27	2E	44	COLDN1
10	4E	61	COLDN2	28	2D	43	2G
11	4D	60	4G	29	---	42	2F
12	---	59	4F	30	---	41	2A
13	---	58	4A	31	2C	40	2B
14	---	57	---	32	DP1	39	1G
15	---	56	---	33	1E	38	1F
16	4C	55	4B	34	1D	37	1A
17	---	54	---	35	1C	36	1B
18	DP3	53	---				

NOTES:

1. DISPLAY: TN STATIC, TRANSPARENT, POSITIVE IMAGE (BLACK CHARACTERS - LIGHT BACKGROUND).
2. OPERATING TEMP: -40 TO +113 DEG C.
3. FRONT POLARIZER TO BE VERTICAL TO BE COMPATIBLE WITH POLARIZED SUNGLASSES.
4. VIEW ANGLE: 1:30
5. PART IS TO BE ROHS COMPLIANT.

<p>700 ACC BLVD RALEIGH, NC 27607 (919) 600-6440 (800) 766-6700 www.lxdinc.com</p>	DESCRIPTION	1.0x6 DIGITS	
	PART NUMBER	H4048D	
INFORMATION CONTAINED HEREIN IS PROPRIETARY TO LXD, AND MAY NOT BE USED OR DISCLOSED WITHOUT THE PERMISSION OF LXD	DRAWING	2219	REV E
UNLESS OTHERWISE SPECIFIED TOLERANCES ARE: MM ±0.25 INCH ±0.01	DRAWN	LJO	DATE 10/24/2003
			SHEET 1 OF 1

DO NOT SCALE