



PIN	FUNC'T	PIN	FUNC'T
1	BP	50	6G
2	6E	49	6F
3	6D	48	6A
4	6C	47	6B
5	DP5	46	5G
6	5E	45	5F
7	5D	44	5A
8	5C	43	5B
9	DP4	42	COLDN2
10	4E	41	4G
11	4D	30	4F
12	4C	39	4A
13	DP3	38	4B
14	3E	37	3G
15	3D	36	3F
16	3C	35	3A
17	DP2	34	COLDN1
18	2E	33	2G
19	2D	32	2F
20	2C	31	2A
21	DP1	30	2B
22	1E	29	28
23	1D	28	1G
24	1C	27	1F
25	1B	26	1A

- NOTES:
1. TN STATIC, REFLECTIVE, POSITIVE IMAGE (BLACK CHARACTERS - LIGHT BACKGROUND).
 2. VIEW ANGLE: 1:30
 3. FRONT POLARIZER TO BE VERTICAL TO BE COMPATIBLE WITH POLARIZED SUNGLASSES.
 4. OPERATING TEMP: -40 TO +113 DEG C.
 5. ROHS COMPLIANT.

<p>7300 ACC BLVD. RALEIGH, NC, 27617 (919) 600-0440 (800) 786-8710 www.lxdinc.com</p>	DESCRIPTION	<p>.70X6 DIGITS</p> <p>H4059C</p>
	PART NUMBER	
INFORMATION CONTAINED HEREIN IS PROPRIETARY TO LXD, AND MAY NOT BE USED OR DISCLOSED WITHOUT THE WRITTEN PERMISSION OF LXD	DRAWING	REV
UNLESS OTHERWISE SPECIFIED TOLERANCES ARE:	LJO	2243
MM ±0.25 INCH ±0.01	DATE	01/07/2004
	SHEET	1 OF 1

DO NOT SCALE