



PIN	FUNCT	PIN	FUNCT
1	BP	40	BP
2	---	39	---
3	---	38	---
4	---	37	4G
5	4E	36	4F
6	4D	35	4A
7	4C	34	4B
8	DP3	33	---
9	3E	32	3G
10	3D	31	3F
11	3C	30	3A
12	DP2	29	3B
13	2E	28	COL
14	2D	27	2G
15	2C	26	2F
16	DP1	25	2A
17	1E	24	2B
18	1D	23	1G
19	1C	22	1F
20	1B	21	1A

NOTES:

1. DISPLAY: TN, TRANSPARENT, POSITIVE IMAGE (BLACK CHARACTERS - LIGHT BACKGROUND).
2. OPERATING TEMP: -40 TO +113 DEG C.
3. POLARIZER: OUTDDOR HIGH STABILITY
4. FRONT POLARIZER TO BE VERTICAL TO BE COMPATIBLE WITH POLARIZED SUNGLASSES.
5. VIEW ANGLE: 1:30
6. ROHS COMPLIANT.

LXD LIQUID CRYSTAL DISPLAYS
2300 ACC BLVD
RALEIGH, NC 27617
(919) 600-6440
(800) 786-8700
www.lxdinc.com

DESCRIPTION: **0.7x4 DIGITS**

PART NUMBER: **H4100B**

DRAWING: **2340** REV: **B**

DRAWN: **LJO** DATE: **11/29/2004** SHEET: **1 OF 1**

DO NOT SCALE

UNLESS OTHERWISE SPECIFIED TOLERANCES ARE: $\text{MM} \pm 0.25$ $\text{INCH} \pm 0.01$